



*20kW & 24kW
Three Phase
Ducted Split*



Find out more at www.greeonline.com



Control System Lineup

- Wire Controller XK46
- Wireless Remote Controller YAP1F (Optional)



Features

- Higher Efficiency
- Compact structure
- CAN Bus communication
- High and Adjustable ESP
- Wide operation ranges for both temp and voltage
- Refrigerant cooling technology
- Optimized fan blade and motor support
- Condenser simulation design



Intelligent defrosting



Compact design



Anti-cold function



Comprehensive protection



Easier maintainability



Self-diagnosis



Wide operation range

| Model | | FGR20Pd/DNa-X | FGR24Pd/DNa-X |
|------------------------------|--------------------------------|-----------------------------|---------------|
| Part Number | | AC5720-I/O | AC5724-I/O |
| Performance | | | |
| Cooling Capacity (range) | kW | 20(10~25) | 24(11~27.5) |
| Heating Capacity (range) | kW | 22.4(10~30) | 26(11~33) |
| Cooling Power Input | kW | 6.06 | 7.12 |
| Heating Power Input | kW | 6.00 | 7.02 |
| AEER | W/W | 3.16 | 3.27 |
| ACOP | W/W | 3.96 | 3.72 |
| Air Flow Volume(Max) | L/sec | 1222 | 1389 |
| Static Pressure (adjustable) | Pa | 0~250 | 0~250 |
| SPL Indoor | dB (A) | 53 | 55 |
| SPL Outdoor | dB (A) | 60 | 62 |
| Electrical | | | |
| Power Supply | 380~415 / 50Hz / 3ph - Outdoor | | |
| Recommended Circuit Breaker | A | 32 | 32 |
| Cooling / Heating | A | 11.2 / 12.3 | 12.7 / 12.5 |
| Indoor Power supply | 230V | 2 Core plus earth (3 cores) | |
| Control Wiring | 2 Core non polar | | |
| Wired Controller | XK46 | | |
| Dimensions and Weights | | | |
| Indoor Dimension (W×H×D) | mm | 1690x440x870 | |
| Indoor Net Weight | kg | 110 | 113 |
| Outdoor Dimension (W×H×D) | mm | 940x1615x460 | |
| Outdoor Net Weight | kg | 155 | 175 |
| Installation | | | |
| Operating Temp Range (Cool) | °C | -7~48 | -7~48 |
| Operating Temp Range (Heat) | °C | -20~24 | -20~24 |
| Refrigerant | | R410a | R410a |
| Refrigerant Charge | kg | 6.7 | 9.5 |
| Pre-charged pipe length | m | 5 | 5 |
| Gas Additional Charge | g/m | 54 | 54 |
| Pipe Connections (Brazed) | mm | 9.52 / 19.05 | 9.52 / 22.22 |
| Max Pipe Height | m | 30 | 30 |
| Max Pipe Length | m | 50 | 70 |
| Condensate drain outlet | mm | 30 | |

Note: Above parameters are for reference only. Actual parameters may vary.



For Installation and Sales:

For Parts and Warranty:

GREE
AIR CONDITIONER

www.greeonline.com
0800 BUY GREE (NZ)
1800 GREE 4 ME (AU)



GREE
NZ & AUS
NOW ON
FACEBOOK!