

Flexible Multi-Core & Multi-Pair Instrumentation Cables – Overall Screened

Application: Internal and external inter-connections of electronic apparatus such as computers, intercoms,

signalling and alarm systems.

Conductor: Annealed Copper Wire

Insulation: PVC V-90

Screen: Aluminium Tape Screen, Polyester Mylar Tape Lapping and 7/0.20 Tinned Copper Drain Wire.

Sheath: PVC 5V-90 BLACK

Standards: AS1125 (Conductor), AS/NZS 3808 (PVC)

Greenstar: Approved

ELECTRA Part Number	PAIRS	SIZE	O.D.
EAS7301P	1	0.55	5.2
EAS7302P	2	0.55	7.5
EAS7303P	3	0.55	8.0
EAS7304P	4	0.55	8.8
EAS7306P	6	0.55	10.4
EAS7308P	8	0.55	11.4
EAS7310P	10	0.55	13.4
EAS7312P	12	0.55	14.2
EAS7316P	16	0.55	15.6
EAS7320P	20	0.55	17.5
EAS7324P	24	0.55	19.8
EAS7336P	36	0.55	22.8

*O.D. ± 10% = mm *Size = mm²

ELECTRA Part Number	PAIRS	SIZE	O.D.
EAS7401P	1	0.88	5.8
EAS7402P	2	0.88	8.5
EAS7403P	3	0.88	9.2

*O.D. ± 10% = mm *Size = mm²

ELECTRA Part Number	PAIRS	SIZE	O.D.
EAS7501P	1	1.50	6.4
EAS7502P	2	1.5	9.5
EAS7503P	3	1.50	10.2
EAS7504P	4	1.5	11.4
EAS7506P	6	1.50	13.7
EAS7508P	8	1.5	15.0
EAS7510P	10	1.5	17.8
EAS7512P	12	1.5	18.4

*0.D. ± 10% = mm *Size = mm²

electracables.com.au

SYDNEY (02) 8786 5200 MELBOURNE (03) 9706 6819

BRISBANE (07) 3386 9800 PERTH (08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38